



NOTES:

1. CONCRETE: 5,000 PSI MINIMUM AFTER 28 DAYS.
2. DESIGN CONFORMS WITH 310 CMR 15.00, DEP TITLE 5 REGS, FOR SEPTIC TANKS.
3. ALL REINFORCEMENT PER ASTM C1227-93.
4. DESIGNED FOR H-20 LOADING, COVER 1-5FT.
5. TONGUE AND GROOVE JOINT SEALED WITH BUTYL RESIN. INLET HEIGHT MAY INCREASE SLIGHTLY DUE TO THE BUTYL RESIN USED.
6. TEES AND BAFFLES SOLD SEPARATELY.

GALLONS	A (HEIGHT)	B (INLET)	C (LIQUID)	WEIGHT (LBS)	ITEM NO.
4,000	76"	58"	48"	56,260	TK-4000C2C
5,000	88"	70"	60"	60,820	TK-5000C2C
5,500	92"	74"	64"	62,230	TK-5500C2C
6,000	96"	78"	68"	63,730	TK-6000C2C
6,500	100"	82"	72"	65,340	TK-6500C2C
7,000	106"	88"	78"	67,470	TK-7000C2C
7,500	112"	94"	84"	69,750	TK-7500C2C
8,000	118"	100"	90"	72,000	TK-8000C2C
8,500	124"	106"	96"	74,280	TK-8500C2C
9,000	130"	112"	102"	76,530	TK-9000C2C
9,500	136"	118"	108"	78,780	TK-9500C2C
10,000	140"	122"	112"	80,300	TK-10000C2C
10,500	146"	128"	118"	82,550	TK-10500C2C
11,000	152"	134"	124"	84,810	TK-11000C2C
11,500	158"	140"	130"	87,070	TK-11500C2C
12,000	162"	144"	134"	88,570	TK-12000C2C

E.F. SHEA
NEW ENGLAND
CONCRETE PRODUCTS, INC.

COMMERCIAL LINE TANK
 2 COMPARTMENT
 4000 TO 12000 GALLON